

ISAM

Display controll unit in TSPCs and info steles from 42 inches upwards

Technical specifications ISAM version 4K	
Video input	1* HDMI: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160P 1* DP: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160P The image source is automatically activated when a signal is received
Output	HDMI, DisplayPort display connection, backlight power supply
OSD	Not available
Note for touch operation	If you purchase a MOStroN device with touch, your media player/mini PC must have at least one USB 2.0 type A port. Supported operating systems: Windows7 and higher, Linux distributions and others on request
Input voltage	100 – 240 VAC 180 Watt max.
Optional	2 x 15 watt audio amplifiers

Technical specifications ISAM Full HD version	
Video input	VGA, DVI, HDMI HDMI: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p DVI: 1920x1200, 60Hz VGA: 640x480 bis 1920x1200, 60Hz
Output	2- or 4-channel LVDS Full HD, backlight power supply
OSD	5 OSD menu button
Note for touch operation	If you purchase a MOStroN device with touch, your media player/mini PC must have at least one USB 2.0 type A port. Supported operating systems: Windows7 and higher, Linux distributions and others on request
Input voltage	100 – 240 VAC 180 Watt max.
Optional	2 x 15 watt audio amplifiers