

ISD2-55

Double-sided Information-Totem with 54,6" 4K Display, Aspect Ratio 9:16, Full Glass Front and optional touch



reddot award 2016
winner



ISD2-55

Double-sided Information-Totem with 54,6"4K Display, Aspect Ratio 9:16, Full Glass Front and optional touch

General Informations	
Application	Digital Signage, digital guidance system, room occupancy system, digital advertising and many more.
Chassis	Black anodised aluminium with a fine brushstroke finish on a sturdy metal base (different coloured powder coating or anodising possible) Top: Glass front made of tempered single-pane safety glass Bottom: Black anodised aluminium with a fine brushstroke finish
Cooling	Convection cooling without fan
Mounting and installation options	Floor mounting with small stand, or portable with tilt-proof stand
Image Sticking	In order to avoid image sticking (burn-in effect) on your display, we recommend that you follow the instructions below: - Try to avoid static contents on your display (don't use it as a simple billboard). After 5 minutes any static screen content should be replaced by a moving picture for at least 10 seconds. - If possible, do not always place your logo or other repetitive contents (e.g. greeting template) in the same place. - If possible, do not always fill the background with the same colour. Plan alternating colours or pictures. Use a moving picture or pure black as a screen saver.

Technical Specification Display	
Display	2 x 54,64"
Display Resolution	3840 x 2160 dots (RGB), aspect ratio 16:9
Display Technology	IPS
Colour Depth	10 bit 1.07 billion colours
Brightness	700 cd/m ²
Backlight	Energy saving LED-edge-backlight
Contrast Ratio	1100:1
Viewing Angle (horizontal/vertical)	178°/178° (89-89/89-89)
Pixel Error Class according to EN ISO 9241-307	II (other classes on inquiry)
Front double-sided	Full glass front with C-edge made of tempered single-pane safety glass or optionally with multi-touch

Technical Specifications	
Dimensions Totem without base	approx. 1928 (H) x 748,7 (W) x 104 (D) mm
Dimensions Totem with floor screw connection (small base)	approx. 8 (H) x 760 (W) x 392 (D) mm If the base cannot be screwed to the floor, please order the tilt-proof base!
Dimensions of the tilt-proof base (large base without floor screw connection)	approx. 8 (H) x 1170 (W) x 1170 (D) mm
Supply Voltage	100 – 240 VAC
Power Consumption	Max. 360 Watts / 2 times 180 Watts
IP-protection class	Complete unit IP20
Permissible operation temperature	+ 5° ~ + 35°C
Permissible operation humidity	0 % ~ 95% (relative humidity, without condensation)
Weight	approx. 160 kg
Noise development	barely perceptible
Power cable	2.0 m IEC connection cable with lock
Device connection	Supply line (network and LAN) possible from below or behind

ISD2-55

Double-sided Information-Totem with 54,6"4K Display, Aspect Ratio 9:16, Full Glass Front and optional touch

Technical Specification of the integrated computer module	
Processor	Intel® Elkhart Lake J6412 Celeron processor 4 cores / base clock 2.0 GHz, max. 2.6 GHz
System Memory	2* SO-DIMM socket for DDR4, 3200 MHz. up to max. 32GB, equipped with 1* 8GB DDR4 SO-DIMM (other capacities optionally available)
Mass Memory	1* M.2 M-key PCIe Gen.3 2242/2280 NVMe + SATA socket equipped with 1* x M.2 2280 NVMe 256GB SSD (other capacities optionally available)
Expansion slots	1* M.2 E-Key 2242/2280, 1* M.2 B-Key 3042 in combination with SIM card slot
Graphics	Intel UHD 10th Gen. Graphic shared Memory
Connections on the back of the built-in computer	1* HDMI 2.0b 1* Audio line-out/MIC combo 3.5mm jack socket 3* USB 3.1 (Gen.2) port, 3 x USB 2.0 port 2* Intel® i225V 2.5GbE 1* IEC connector (C13 socket) 1* Power button, LEDs for power, HDD
BIOS	AMI-BIOS UEFI with integrated LAN boot ROM image
Watchdog-Timer	Timeout intervals from 10 sec. - 255 min. (requires trigger software)
System Monitoring	CPU and system temperature, internal operating voltages
Safety	TPM2.0 onboard
Operating System	Windows 10 IOT / Professional, Windows 11 IOT / Professional compatible Linux distributions on request Note: The customer is responsible for operating system maintenance and updates.

Technical specifications of the optional Intel Core i5 upgrade computer	
Processor	Intel® Whiskey Lake Core i5 8365U CPU 4 cores / Base clock 1.6 GHz, max. 4.1 GHz
System Memory	2* SO-DIMM socket for DDR4, 3200 MHz. up to max. 32GB, equipped with 1* 8GB DDR4 SO-DIMM (other capacities optionally available)
Mass Memory	1* M.2 M-key PCIe Gen.3 2242/2280 NVMe + SATA socket equipped with 1* x M.2 2280 NVMe 256GB SSD (other capacities optionally available)
Expansion slots	1* M.2 E-Key 2230 with Intel CNVi
Graphics	Intel UHD 8th Gen. Graphic shared Memory
Interfaces on the backside	1* HDMI 1.4 1* Audio line-out 3.5mm jack socket 4* USB 3.1 (Gen.2), 1 USB3.1 (Gen2) Type C 1* Intel® i219LM 1GbE 1* Intel® i225V 2.5GbE 1* IEC connector (C13 socket) 1* Power button, LEDs for power, HDD
BIOS	AMI-BIOS UEFI with integrated LAN boot ROM image
Watchdog-Timer	Timeout intervals from 10 sec. - 255 min. (requires trigger software)
System Monitoring	CPU and system temperature, internal operating voltages
Safety	TPM2.0 onboard
Operating System	Windows 10 IOT / Professional, Windows 11 IOT / Professional compatible Linux distributions on request Note: The customer is responsible for operating system maintenance and updates.

ISD2-55

Double-sided Information-Totem with 54,6"4K Display, Aspect Ratio 9:16, Full Glass Front and optional touch

Technical specifications of ISAM	
Inputs for image signal	1* HDMI: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160P 1* DP: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160P The image source is automatically activated when a signal is received.
Power supply	1* IEC connector (C13 socket)
Audio Option	Optionally available audio amplifier with 2 x 15 watt power output

Configuration	
ISD-55-BPL	Small base for floor mounting
ISD-55-BPG	Large tilt-proof base for mobile use
ISD-OPT-WLAN ₂	Intel Wireless-AC 9260, 2.4Ghz / 5Ghz with Bluetooth 5 WLAN standards: IEEE 802.11a/b/g/n/ac Encryption: WPA, WPA2, WPA3 Antenna position on the top or bottom of the device with 2 28mm antennas, WLAN only possible with surface mounting!
ISD-55-Touch	Rear glass touch, projected capacitive 10-finger multi-touch (PCT) with internal USB connection
ISD-OPT-AUDIO ₁	Audio option with hidden structure-borne sound transducers 2x15 watts
ISD-OPT-Acin-2	Optional power unit with RCD and 2 earthed sockets Recommended for version with ISAM and own player / PC
Pre-installed operating system (except for ISAM)	Win10 /11 IoT Optional upgrade to Windows 10 /11 Professional, possible without operating system or installing a customer image