

TSPC-4-32

MOSTRON^{ELEKTRONIK}

Panel PC with 31,5" display in 16:9 format, full glass front, optionally with touch, built-in and surface-mounted version



MOSTron Elektronik GmbH · Helmholtzstraße 20 · D-41747 Viersen · www.mostron.de · info@mostron.de · Fon +49(0)2162 3798-0

Alle verwendeten Logos und Firmennamen sind Warenzeichen oder eingetragene Warenzeichen der jeweiligen Firmen. Irrtümer, Druckfehler, sowie technische Änderungen vorbehalten. All logos and company names are trademarks or registered trademarks of their respective owners. No liability for errors and misprints. Subject to change.

Stand: 02/2026



Panel PC with 31,5" display in 16:9 format, full glass front, optionally with touch, built-in and surface-mounted version

General Information	
Application	Digital Signage, digital guidance system, room occupancy system, digital Advertising.
Chassis	Brushed chrome steel with full glass front Optional powder-coated steel housing in RAL colour
Cooling	Via the design-related shadow gap for flush-mounted installation No additional installation volume is required. Integrated cooling unit with long-life fans for use even under difficult ambient conditions.
Mounting and installation options	Surface-mounted with (wall) mounting plate; Flush-mounted with mounting frame
Image Sticking	In order to avoid image sticking (burn-in effect) on your display, we recommend that you follow the instructions below: • Try to avoid static contents on your display (don't use it as a simple billboard). After 5 minutes any static screen content should be replaced by a moving picture for at least 10 seconds. • If possible, do not always place your logo or other repetitive contents (e.g. greeting template) in the same place. • If possible, do not always fill the background with the same colour. Plan alternating colours or pictures. Use a moving picture or pure black as a screen saver

Technical Specification Display	
Display	31,5"
Display Resolution	1920 x 1080 dots (RGB), aspect ratio 16:9
Colour Depth	16,7 Mio colours (True Colour)
Brightness	500 cd/m ²
Backlight	Energy saving LED-edge-backlight
Contrast Ratio	3000:1
Viewing Angle (horizontal/vertical)	178° /178° (89-89/89-89)
Pixel Error Class according to EN ISO 9241-307	II (other classes on inquiry)
Front	Full glass front with C-edge made of tempered single-pane safety glass with PC multi-touch

Technical Specification	
Dimensions surface-mounted version incl. wall mounting plate	approx. 446 (H) x 751 (W) x 72(D) mm
Dimensions flush-mounted version with mounting frame	approx. 471 (H) x 776 (W) x 72 (D) mm (dimension including all-round ventilation gap and frame)
Size of the installation opening (for drywall/wood/stone wall)	
Installation frame mounted from the rear ('A')	approx. 471,2 (H) x 776,2 (W) x 100 (D) mm
Installation frame mounted from the front ('B')	approx. 473,9 (H) x 778,9 (W) x 100 (D) mm
Supply Voltage	100 – 240 VAC
Power Consumption	approx. 55 W (basic), approx. 60 W (upgrade computer)
IP-protection class	complete unit IP20
Permissible operation temperature	+ 5° ~ + 35°C
Permissible operation humidity	0 % ~ 95% (relative humidity, without condensation)
Weight	approx. 18 kg
Noise development	barely perceptible
Power cable	2.0m IEC connection cable with lock

Panel PC with 31,5" display in 16:9 format, full glass front, optionally with touch, built-in and surface-mounted version

Technical Specification of the integrated computer module	
Processor	Intel® Elkhart Lake J6412 Celeron processor 4 cores / base clock 2.0 GHz, max. 2.6 GHz
System Memory	2* SO-DIMM socket for DDR4, 3200 MHz. up to max. 32GB, equipped with 1* 8GB DDR4 SO-DIMM (other capacities optionally available)
Mass Memory	1* M.2 M-key PCIe Gen.3 2242/2280 NVMe + SATA socket equipped with 1* x M.2 2280 NVMe 256GB SSD (other capacities optionally available)
Expansion slots	1* M.2 E-Key 2242/2280, 1* M.2 B-Key 3042 in combination with SIM card slot
Graphics	Intel UHD 10th Gen. Graphic shared Memory
Interfaces on the backside	1* HDMI 2.0b 1* Audio line-out/MIC combo 3.5mm jack socket 3* USB 3.1 (Gen.2) port, 3 x USB 2.0 port 2* Intel® i225V 2.5GbE 1* IEC connector (C13 socket) 1* Power button, LEDs for power, HDD
BIOS	AMI-BIOS UEFI with integrated LAN boot ROM image
Watchdog-Timer	Timeout intervals from 10 sec. - 255 min. (requires trigger software)
System Monitoring	CPU and system temperature, internal operating voltages
Safety	TPM2.0 onboard
Operating System	Windows 10 IOT / Professional, Windows 11 IOT / Professional compatible Linux distributions on request Note: The customer is responsible for operating system maintenance and updates.

Configuration Options	
TSPC4-32-WM	Wall mounting plate for surface mounting
TSPC4-32-UMK	Flush-mounted installation set for flush wall installation
TSPC-OPT-WLAN2	Intel Wireless-AC 9260, 2.4Ghz / 5Ghz with Bluetooth 5 WLAN standards: IEEE 802.11a/b/g/n/ac Encryption: WPA, WPA2, WPA3 Antenna position on the top or bottom of the device with 2 28mm antennas, WLAN only possible with surface mounting!
TSPC-OPT-SO1	Lock option to secure the device for surface mounting
TSPC-32-Touch	Rear glass touch, projected capacitive 10-finger multi-touch (PCT) with internal USB connection
Pre-installed operating system	Win10 /11 IoT Optional upgrade to Windows 10 /11 Professional, possible without operating system or installing a customer image

TSPC-4-32

Panel PC with 31,5" display in 16:9 format, full glass front, optionally with touch, built-in and surface-mounted version

Technical specifications of the optional Intel Core i5 upgrade computer	
Processor	Intel® Whiskey Lake Core i5 8365U CPU 4 cores / Base clock 1.6 GHz, max. 4.1 GHz
System Memory	2* SO-DIMM socket for DDR4, 3200 MHz. up to max. 32GB, equipped with 1* 8GB DDR4 SO-DIMM (other capacities optionally available)
Mass Memory	1* M.2 M-key PCIe Gen.3 2242/2280 NVMe + SATA socket equipped with 1* x M.2 2280 NVMe 256GB SSD (other capacities optionally available)
Expansion slots	1* M.2 E-Key 2230 with Intel CNVi
Graphics	Intel UHD 8th Gen. Graphic shared Memory
Interfaces on the backside	1* HDMI 1.4 1* Audio line-out 3.5mm jack socket 4* USB 3.1 (Gen.2), 1 USB3.1 (Gen2) Type C 1* Intel® i219LM 1GbE 1* Intel® i225V 2.5GbE 1* IEC connector (C13 socket) 1* Power button, LEDs for power, HDD
BIOS	AMI-BIOS UEFI with integrated LAN boot ROM image
Watchdog-Timer	Timeout intervals from 10 sec. - 255 min. (requires trigger software)
System Monitoring	CPU and system temperature, internal operating voltages
Safety	TPM2.0 onboard
Operating System	Windows 10 IOT / Professional, Windows 11 IOT / Professional compatible Linux distributions on request Note: The customer is responsible for operating system maintenance and updates.